```cpp
//  file: nan_test.cpp
//
//  Program to test when programs compiled with g++ return nan's and inf's
//
//  Programmer:  Dick Furnstahl  furnstahl.1@osu.edu
//
//  Revision history:
//     01/24/04  original version, translated from nan_test.c
//     02/01/04  added log(-1.)
//     01/20/06  added examples of combining nan's and inf's
//
//  Notes:
//   * "nan" stands for "not a number"
//   * "inf" stands for infinity
//   * -Werror removed from make_nan_test to allow it to proceed with
//      warning (which may not occur anyway)
//   * If we explicitly put 0. in a denominator, we would get a compiler
//      warning.  But defining denominator=0. and then using it gets
//      no warning!  (So you can't rely on the compiler for this.)
//
//  To do:
//
///******************************************************************

// include files
#include <iostream>            // note that .h is omitted
#include <iomanip>             // note that .h is omitted
#include <string>
using namespace std;
#include <cmath>

//************************** main program **************************
int
main (void)
{
  cout << "Fun and games with nan's and inf's: " << endl;

  double numerator = 1.;
  double denominator = 0.;

  cout << " 1./0. ==> " << numerator/denominator << endl;
  cout << " -1./0. ==> " << -numerator/denominator << endl;

  cout << " log (0.) ==> " << log(0.) << endl;

  cout << " sqrt(-1.) ==> " << sqrt(-1.) << endl;

  cout << " log(-1.) ==> " << log(-1.) << endl;

  // Now let's try some predictions

  cout << endl << "Now try predicting.  In each case, predict nan or inf."
       << endl << endl;
  string answer;      // define a C++ string to hold the answer

  cout << " log(exp(exp(10.))) ==> " ;
  cin >> answer;
  cout << "You answered " << answer << ". The correct answer is: "
       << log(exp(exp(10.))) << endl << endl;

  cout << " arccos(2) ==> " ;
  cin >> answer;
  cout << "You answered " << answer << ". The correct answer is: "
       << acos(2.) << endl << endl;

  // Now let's try combining
  double my_inf = numerator/denominator;
  double my_nan = sqrt(-1.);
```

```cpp
  cout << " add 1 to an inf ==> ";
  cin >> answer;
  cout << "You answered " << answer << ". The correct answer is: "
       << (my_inf + 1.) << endl << endl;

  cout << " multiply an inf by 10 ==> ";
  cin >> answer;
  cout << "You answered " << answer << ". The correct answer is: "
       << 10.*my_inf << endl << endl;

  cout << " add an inf to a nan ==> ";
  cin >> answer;
  cout << "You answered " << answer << ". The correct answer is: "
       << (my_inf + my_nan) << endl << endl;

  cout << " add +inf to -inf ==> ";
  cin >> answer;
  cout << "You answered " << answer << ". The correct answer is: "
       << (my_inf - my_inf) << endl << endl;

  return 0;
}
```